



COUNTERTOP FRYERS



LD56 fryer

KEY FEATURES

- Two models availability
- *choose to suit your level of business*
- One-piece, stainless steel plunged hob and pan
- *easy to clean*
- Easy to remove element box(es)
- *stand up to rigorous use*
- Supplied with 13A plug(s)
- *plug and use straight out of the packaging*

MODELS and ACCESSORIES

LD50 single pan fryer (7 litre)

LD56 twin pan fryer (2 x 7 litre)

- No accessories

MODEL DIMENSIONS (in mm)

LD50 : 300mm (w) x 630mm (d) x 315mm (h)

LD56 : 600mm (w) x 630mm (d) x 315mm (h)

SPECIFICATION DETAILS

	LD50	LD56
Rating (kW)	2.75	2 x 2.75
Supply voltage	230V~	230V~
Current split (amps)	L1: 13	L1: 2 x 13
Chip output (kg per hour)	8.5	17
No. of baskets	1	2
Weight (kg)	12.5	25
Packed weight (kg)	14	26

INSTALLATION NOTES

Adequate ventilation must be provided to supply sufficient fresh air and to allow easy removal of any such products that may present a risk to health.

Please consult current legislation for details that relate to specific locations.

Install unit on a level, fireproof surface in a well-lit position. A clearance of 150mm should be observed between appliance and any combustible wall.

