F900 SERIES

G9440 Gas Radiant Chargrill





Short Form Specification

Unit to be Falcon F900 Series high performance gas chargrill having extended cooking zone with single cast iron 8.4kW burner. Unit to be supplied upon adjustable feet or installed upon open stand. Unit will be fitted with removable stainless steel splashguard to the rear and sides.

The unit will have cast iron burner radiants to protect burners and to offer improved heat transfer to cast iron brander bars. Burners to have variable heat settings with heat being distributed evenly.

The cast iron brander bars will be a nominal 100mm wide each and cover the full cooking surface – allowing a food resting area at the front section. The bars will be reversible and designed to ensure that grease can flow from food into the full length pressed drip trough and then into the large capacity container.

The hob will be constructed from 2mm 304 grade stainless steel. Hobs will be laser cut with right-angled edges to allow joining of units with no gaps between hobs. Exterior panels are Scotch Brite finish stainless steel. Control knobs to be marked showing gas positions and to have a bezel behind each knob to prevent water ingress.

Unit will be for use with natural, propane or butane gas and be supplied with conversion kit.

Key Features

- 8.4kW cast iron burner with protective radiants
- Extended cooking area
- Pressed grease collection tray at hob front
- Removable stainless steel surround
- Cast iron, reversible brander bars
- Large capacity grease collection container
- Cast iron urners with variable control/turndown position
- Supplied upon stainless steel adjustable feet
- Full width debris collection tray
- 2mm thick 304 grade stainless steel hob
- Laser cut hob allows edge to edge joining of units
- Stainless steel external panels with Scotch Brite finish
- For use with natural, propane and butane gas. Conversion kit supplied with each unit
- Dynamic Link System Compatible



Integrated linking system allows quick and easy installation to create a continuous cookline. *Patent pending, application no. GB 1511389.7*

Optional Accessories

- Cast iron lift-off griddle plate
- Front hob rail
- Fixed or mobile stand

G9440 Gas Radiant Chargrill

Model Dimensions (mm)



400 400 900 175 gas inlet jođ <u>-</u>_@ 350 Clanna anadan Cb ⊒ᡎ 40 gas inlet 575 gas inlet The unit can be connected at 40 gas inlet the rear or from below. 40 gas inlet 725 gas inlet 006 575 gas inlet

Specification Details

	Natural Gas	Propane Gas	Butane Gas
Total rating (kW - Nett)	8.4	9	9
Total rating (btu/hr - gross)	28,660	30,708	30,708
Inlet size	3/4" BSP	3/4" BSP	3/4" BSP
Flow rate	0.83m³/hr	0.65kg/h	0.64kg/h
Inlet pressure (mbar)	20	37	29
Operating pressure (mbar)	15	37	29
Burner rating (kW - Nett)	8.4	9	9
Burner rating (btu/hr - gross)	28,660	30,708	30,708
Weight (kg)	55	55	55
Packed weight (kg)	63	63	63
Packed dimensions (mm)	450 (w) x 970 (d) x 880 (h)		

Installation Note: Please consult local legislation with regard to installation of cooking equipment.