

EB3FX/TT - Lincat FilterFlow FX Countertop Automatic Fill Twin-Temperature Water Boiler - W 250 mm - 3.0 kW

- Twin tank model, tanks can be set to different temperatures - ideal for brewing black teas at 98°C and green teas at 71°C
- Lockable mode prevents water being dispensed without the input of a PIN code, perfect for schools, prisons, care homes and settings with vulnerable individuals
- Narrow 250mm footprint saves valuable counter space without compromising capacity or performance
- Built-in water filtration system improves water quality and reduces scale build-up. High volume, easy change FilterFlow cartridge

The FilterFlow Automatic Water Boiler comes with a twin tank, allowing you to set two different temperatures for the perfect cup of tea.

- Easily operated from a large, colour touchscreen display. Menu navigation is quick and easy with the temperature and timer simple to adjust
- Eco setting reduces the volume of boiling water by 50% for quieter periods. The intelligent predictive eco setting learns usage patterns and switches between eco mode and standard mode to deliver the required hot water output in the most economical way
- 7-day timer allows the boiler to be programmed to switch off overnight or at weekends to conserve energy
- Enhanced diagnostics identify possible causes. The on screen diagnostic information will enable the engineer to identify the parts needed and repair your water boiler at first visit

15.0

Specifications

Summary		Power and Performance	
Brand	Lincat	Total Power kW	3.0
Range	FilterFlow	Temperature Range °C	70-98
Series	FX Counter-top Boiler	IP Rating	IP23
Power Type	Electric	Hourly Output Litres	25
Unit Type	Counter-top	Hourly Output Cups	125
Available in UK Only	No	Temperature Control	Electronic
UK Warranty	2 Years Parts and Labour Warranty		
Export Warranty	Contact your local dealer		
GTIN	5056105101390		
Key Specifications		Capacity	
Outlet	Twin Tap	Hot and Cold Water Output	No
Dispense Lock	No	Rapid Draw Off Litres	2×4.5
WRAS Approved	Yes	Rapid Draw Off Cups	45

Capacity Litres



hingatot found til territown Goto Uppe unknown

Weights and Dimensions		Supply Connections	
Unit Height (External) mm	596	Requires Installation	No
Unit Width (External) mm	250	Requires Electrical Supply	Yes
Unit Depth (External) mm	525	UK 3 Pin Plug	Yes
Net Weight Kg	17.1	Requires Hardwiring	No
		Electrical Supply Rating Watts	3,000
		Single Phase Amps	13
		Single Phase Voltage	230
		Water Connection Pressure Bar	6
		Water Connection	3/4"

Shipping


Packed Weight Kg	19.7
Packed Height cm	53
Packed Width cm	69.5
Packed Depth cm	36.6


Available Accessories		
BR55	EB3FX AND EB4FX WALL BRACKET	
DP10	DESCALER POWDER	
FC04	Filter Cartridge for Lincat FilterFlow Water Boiler	

Technical Picture









Lincat frifri

Lincat Limited

Whisby Road, Lincoln, LN6 30Z,

United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 503250 Email: export@lincat.co.uk

Opening Hours

Monday – Friday: 8.30am – 5pm