

KEY FEATURES

- Digital temperature display
- Quiet and energy efficient
- Ideal where space is an issue
- Ideal for undercounter storage of your food
- Perfect for student accommodation & smaller commercial kitchens

EXTRA SPEC DETAILS

- Power Required – 13 amp
- Type of defrost - Manual
- Refrigerant -
 - Chillers - R600A
 - Freezers - R290A
- Static cooling -
 - Chiller – Off Cycle
 - Freezer – Manual
- External Finish – White painted mild steel, "S" models are stainless steel
- Internal Finish – White
- Maximum ambient – 30°C / 55% RH
- Adjustable feet

Undercounter Chillers & Freezers



HV200TN



HVS200TN



Model	Dimensions (wxdxh) mm	Temperature	Net Weight Kg	Capacity Litres / cu ft	Shelves	Electrical Consumption Watts	See Price List
HV200TN	600 x 615 x 850	0 / +10°C	35	200	2	100	
HVS200TN	600 x 615 x 850	0 / +10°C	35	200	2	100	
HV200BT	600 x 615 x 850	-18 / -22°C	38	200	2	130	
HVS200BT	600 x 615 x 850	-18 / -22°C	38	200	2	130	

Energy Rating

B

B

B

B

Upright Chillers & Freezers



HV400TN



HVS400TN



HV600BT



HVS600BT

KEY FEATURES

- 400 and 600 litre models available in white or stainless steel exterior
- Ideal for light duty usage
- 600 litre models will take a 2/1 GN shelf
- Clear LED digital display

EXTRA SPEC DETAILS

- Power Required – 13 amp
- Type of defrost - Manual
- Refrigerant -
 - Chillers - R600A
 - Freezers - R290A
- Static cooling –
 - Chiller – Off Cycle
 - Freezer – Manual
- External Finish – White painted mild steel, “S” models are stainless steel
- Internal Finish – White
- Maximum ambient – 30°C / 55% RH
- Adjustable feet



Model	Dimensions (wxdxh) mm	Temperature	Net Weight Kg	Capacity Litres / cu ft	Shelves	Electrical Consumption Watts	See Price List
HV400TN	600 x 615 x 1860	0 / +10°C	68	400	4	161	
HVS400TN	600 x 615 x 1860	0 / +10°C	68	400	4	161	
HV400BT	600 x 615 x 1860	-18 / -22°C	72	400	6	184	
HVS400BT	600 x 615 x 1860	-18 / -22°C	72	400	6	184	

Energy Rating
C
C
C
C

Model	Dimensions (wxdxh) mm	Temperature	Net Weight Kg	Capacity Litres / cu ft	Shelves	Electrical Consumption Watts	See Price List
HV600TN	775 x 750 x 1860	0 / +10°C	93	600	4	207	
HVS600TN	775 x 750 x 1860	0 / +10°C	93	600	4	207	
HV600BT	775 x 750 x 1860	-18 / -22°C	97	600	6	230	
HVS600BT	775 x 750 x 1860	-18 / -22°C	97	600	6	230	

Energy Rating
B
B
C
C